

DATA SHEET

Cable connector



Part Number

5051.N.PRC.09.133

Description

N, Plug, Right angle, Cable

Interface Standard

IEC 60169-16

Suitable Cable

RG142B/U, RG223/U, RG400U



Electrical Data

Impedance	50	Ω		
Max. operating frequency	12.4	GHz	cable limited	
Frequency range	DC to 1GHz	1 to 2.2GHz	2.2 to 3GHz	3 to 6GHz
VSWR	≤1.06	≤1.06	≤1.08	≤1.10
Insertion loss	0.03 $\sqrt{f(\text{GHz})}$	dB		
Insulation resistance	≥5000	MΩ		
Center contact resistance	≤1	mΩ		
Outer contact resistance	≤0.25	mΩ		
Dielectric withstanding voltage	≥1000	Vrms @ 50Hz	cable limited	
Working voltage	≤400	Vrms @ 50Hz	cable limited	

Mechanical Data

Mating cycles	≥500	
Center contact axial force	≥28	N
Center contact axial torque	≥--	Nm
contact gauge ret. Force	≥0.56	N
Center contact	solder	
Outer contact	crimp	
Cable retention force		
RG142B/U	≥257.5	N
RG223/U	≥257.5	N
RG400/U	≥257.5	N

Environmental Data

Operating temperature	restricted by cable and/or silicone used
2002/95/EC (ROHS)	compliant
Sealing	N/A
Thermal shock	MIL-STD-202 Method107, condition B
Moisture resistance	MIL-STD-202 Method106
Corrosion resistance	MIL-STD-202 Method101, condition B
Vibration	MIL-STD-202 Method204, condition D
Shock	MIL-STD-202 Method213, condition I

Material Data

Piece Parts	Material	Surface Plating
center contact	Brass	Au
outer contact	Brass	CuSnZn
body	Brass	CuSnZn
insulator	PTFE	
Ferrule	Brass	CuSnZn
O-ring	silicone rubber	

Zeeteq the technoledge connecting people

No. 51 Sci.-Tech Industry Park, Huoju
Road, SND, Suzhou, China
Zip: 215009

Tel: +86 512 6807 8808
Fax: +86 512 6807 8818
www.zeeteq.com

Rev.: a
iussed: 2008-6-23
page: 1 of 1