

# DATA SHEET

## Cable connector



### Part Number

5044.N.PSC.12.133

### Description

N, Plug, Straight, Cable Mount

### Interface Standard

IEC 60169-16

### Suitable Cable

RG214/U, RG225/U, RG393/U



### Electrical Data

Impedance	50	Ω		
Max. operating frequency	6	GHz	<b>cable limited</b>	
Frequency range	DC to 1GHz	1 to 2.2GHz	2.2 to 3GHz	3 to 6GHz
VSWR	≤1.05	≤1.08	≤1.08	≤1.22
Insertion loss	0.05 $\sqrt{f(\text{GHz})}$	dB		
Insulation resistance	≥5000	MΩ		
Center contact resistance	≤1	mΩ		
Outer contact resistance	≤0.25	mΩ		
Dielectric withstanding voltage	≥2500	Vrms @ 50Hz	cable limited	
Working voltage	≤1000	Vrms @ 50Hz	cable limited	

### Mechanical Data

Mating cycles	≥500	
Center contact axial force	≥28	N
Center contact axial torque	≥0.03	Nm
contact gauge ret. Force	≥0.56	N
Center contact	solder	
Outer contact	crimp	
Cable retention force		
-RG214/U, RG393/U	≥447.5	N
-RG225/U	≥553.7	N

### Environmental Data

Operating temperature	restricted by cable and/or silicone used
2002/95/EC (ROHS)	compliant
Sealing	N/A
Thermal shock	MIL-STD-202 Method107, condition B
Moisture resistance	MIL-STD-202 Method106
Corrosion resistance	MIL-STD-202 Method101, condition B
Vibration	MIL-STD-202 Method204, condition D
Shock	MIL-STD-202 Method213, condition I

### Material Data

<u>Piece Parts</u>	<u>Material</u>	<u>Surface Plating</u>
center contact	Brass	Au
body	Brass	CuSnZn
insulator	PTFE	
ferrule	Brass	CuSnZn
nut	Brass	CuSnZn
gasket	silicone rubber	

**Zeeteq** the technoledge connecting people

No. 51 Sci.-Tech Industry Park, Huoju  
Road, SND, Suzhou, China  
Zip: 215009

Tel: +86 512 6807 8808  
Fax: +86 512 6807 8818  
[www.zeeteq.com](http://www.zeeteq.com)

Rev.: a  
issued: 2008-5-06  
page: 1 of 1